

YANTON®

PROFESSIONAL FM TRANSCEIVER

PROFESSIONAL FM TRANSCEIVER

T-380

OLED HD DISPLAY

Frequency Range

136-174MHz or 400-480MHz

- 2*250 Memory Channels
- Single band standby or dual band standby selection
- One key create group, exit group;
- High/Low Power Selective 5W/1W
- Scrambler
- Bluetooth (optional)



YANTON®

PROFESSIONAL FM TRANSCEIVER

PROFESSIONAL FM TRANSCEIVER

T-380



- 2*250 Memory Channels
- Single band standby or dual band standby selection
- One key create group, exit group;
- High/Low Power Selective 5W/1W
- Scrambler
- Bluetooth (optional)

SPECIFICATION

GENERAL		TRANSMIT PART	
Frequency Range	VHF: 136~174MHz UHF: 400~480MHz	RF Power	5W
Operating Temperature	-20°C~+60°C	Modulate Mode (W/N)	16KΦF3E, 11KΦF3E
Frequency Combination	Phase lock frequency synthesizer	Max. Freq. Deviation (W/N)	<5K / <2.5KHz
Frequency Stability	±2.5ppm	Remain Wave Radiation	<-60dB
Memory Channel	2×250 Channels	Transmitting Current	≤1300mA
Working voltage	DC 7.4V	RECEIVE PART	
Antenna Impedance	50Ω	Sensitivity	<0.25μV(12dB SINAD)
Operating Mode	Simplex of co-frequency or alien frequency	Squelch Sensitivity	<0.20μV
Dimension	125mm×65mm×35mm	Intermodulation Antijamming	50dB
Weight	150g (Include Battery Pack)	Audio Power output	500mW
		Receiving Current	≤100mA
		Squelch Standby	20mA

Notice: Saving your presence, no additional notice will be sent if specification changes because of technology-improving.